

TECHNICAL DATA SHEET

Part No. 411-52480
Article No. 411-52480
Type 1152-4-G



Helashrink 1100 series, with rib - VG style, provides strain relief for harness systems when used in conjunction with a circular grooved adaptor. For VG shapes according to T06 with portholes add "P" after the part number.

Material	Polyolefin, cross-linked (PO-X)
Shrink Ratio	up to 3:1
Min. Shrink Temperature	+275 °F (+135 °C)
Operating Temperature	-103°F to +302°F (-75°C to +150°C)
Dielectric Strength	14 kV/mm
Flammability	ASTM D635
Use Conditions	For Indoor Use Only
Color	Black (BK)
Pkg. Qty.	1

Flexibility	Semi rigid
Angle	90 °
Dielectric Strength	14 kV/mm
H Recovered Dia. Max. b (imperial)	0.41 "
H Recovered Dia. Max. b (metric)	10.5 mm
H Supplied Dia. Min. a (imperial)	0.94 "
H Supplied Dia. Min. a (metric)	24.0 mm
J Recovered Dia. Max. b (imperial)	.23 "
J Recovered Dia. Max. b (metric)	6.0 mm
J Supplied Dia. Min. a (imperial)	.94 "
J Supplied Dia. Min. a (metric)	24.0 mm
Shrink Ratio	up to 3:1
S Nominal Length (imperial)	.39 "
S Nominal Length (metric)	10.0 mm
Tensile Strength	15 MPa

