

B5 series basic switches are miniature in size and feature up to 10 amps switching capability of 100,000 cycles. Mechanical life is one million cycles.

The molded housing is rugged and structurally stable. The terminals are sealed against solder flux entering the switch and are bright acid tin plated for excellent solderability.

Features:

- Up to 10 amps switching capability
- High contact pressure
- Precision operating points
- Button accepts actuation directly from cam
- Constructed in accordance with MIL-PRF-8805/7
- Available in Commercial & Military grades
- Choice of four standard terminal styles or wire leads
- UL recognized & CSA certified
- B5-21141 qualified to MS27217-1
- RoHS/WEEE/Reach compliant



Solder
Terminal Style



Standard Characteristics/Ratings:

ELECTRICAL RATINGS:

Circuitry	Load	Sea Level @ 28VDC	70,000 feet @ 28VDC	Sea Level @ 115VAC, 60Hz
SPNO-DB & SPNC-DB	Resistive	10A	10A	10.1A
	Inductive*	7.5A	3.5A	5A
	Lamp	1A	N/A	3A
SPDT-DB 2 Circuit	Resistive	10A	10A	10.1A
	Inductive*	5A	2A	5A
	Lamp	3A	N/A	1.5A
SPDT	Resistive	10A	10A	10.1A
	Inductive*	3A	1.5A	N/A
	Lamp	3A	N/A	N/A

*L/R = 0.026

DWV	1000Vrms	400Vrms
Electrical Life:	100,000 cycles	
Mechanical Life:	1,000,000 cycles	
Seal:	Unsealed	
Operating Temp Range:	-65°C to +125°C	
Operating Force:	5 oz, +3/-2 oz or 6 oz max or 3 oz min	
Release Force:	2 oz min	
Operate Point:	0.406 +/- 0.010 inches from mounting holes	
Overtravel:	0.012 inches min	
Movement Differential:	0.020 +/- 0.005 inches	
Pretravel:	0.050 inches max	
MATERIALS:		
Case:	Thermoset, blue	
Cover:	Thermoset, blue	
Button:	Thermoplastic, black	
Terminals:	Brass with bright acid tin plating	
Contacts:	Stationary: Silver with gold Moveable: Silver with gold	
Terminal Hardware:	None provided, optional wires	
Mounting Hardware:	None provided	

B5 PART NUMBER CODE


B5	-	X	X	X	X	X
Model		Terminal Style or Wire Length	Operating Force	Circuitry		Contact Material
1. Commercial 2. Military		1. Solder 2. Taper Tab Quick Connect 3. 0.110 Quick Connect ① 4. PC Pin A. With Wires 06.0" lg. B. With Wires 12.0" lg. C. With Wires 18.0" lg. D. With Wires 24.0" lg. E. With Wires 30.0" lg.	1. 5 ⁺³ / ₋₂ oz 2. 6 oz max 3. 5 oz min	1. SPNO-DB, Form X 2. SPNC-DB, Form Y 3. SPDT, Form C 4. SPDT-DB, Form Z		1. Silver/Gold – High Current 2. Silver/Gold – Low Current

① Mates with AMP Series 110 receptacles.


MINIATURE BASIC SWITCHES

B5
BASIC
SWITCHES


DOUBLE BREAK, SNAP-ACTION COMMERCIAL & MILITARY GRADES, MINIATURE




**TERMINAL STYLE 1
SOLDER**





**TERMINAL STYLE 2
TAPER TAB Q. C. TERMINALS
MATES W/AMP SERIES
78 RECEPTACLES**



**TERMINAL STYLE 3
.110 QUICK CONNECT
TERMINALS MATES/AMP
SERIES 110 RECEPTACLES**



**TERMINAL STYLE 4
PRINTED CIRCUIT PINS**



WIRE LENGTH CODE	DIM. "X"	DIM. "Y"
A	06.00±.38	06.09±.38
B	12.00±.50	12.09±.50
C	18.00±.50	18.09±.50
D	24.00±.50	24.09±.50
E	30.00±.75	30.09±.75

TERMINAL NO.	WIRE COLOR
1	BROWN
2	YELLOW
3	RED
4	BLUE

